



RECOMMENDED PCB LAYOUT



MATING DRAW REF

REVISIONS				
LTR	DESCRIPTION	DATE	DWN	APVD
A	RELEASED	01Jan16	AW	WK

ELECTRICAL:
 VLOTAG RATING:50V AC(RMS)/DC
 CURRENT RATING:0.5A AC(RMS)/DC
 CONTACT RESISTANCE:90MΩ MAX
 INSULATION RESISTANCE:500MΩ MIN
 DIELECTRIC WITHSTANDING VOLTAGE:150V
 AC R.M.S
 OPERTING TEMPERATURE:-30°C~+80°C
 MATERIRLS
 HOUSING:HIGH TEMPERATURE PLASTIC
 UL94V-0
 TERMINAL:COPPER ALLOY
 CONTACT:PHOSPHOR BRONAE,GOLD PLATING;

No. of Contacts	Dimensions			
	A	B	C	D
10 (2*5)	6.0	4.9	3.2	4.9
12 (2*6)	6.8	5.7	4.0	5.7
14 (2*7)	7.6	6.5	4.8	6.5
16 (2*8)	8.4	7.3	5.6	7.3
18 (2*9)	9.2	8.1	6.4	8.1
20 (2*10)	10.0	8.9	7.2	8.9
24 (2*12)	11.6	10.5	8.8	10.5
26 (2*13)	12.4	11.3	9.6	11.3
28 (2*14)	13.2	12.1	10.4	12.1
30 (2*15)	14.0	12.9	11.2	12.9
32 (2*16)	14.8	13.7	12.0	13.7
50 (2*25)	22.0	20.9	19.2	20.9

YL007-011-XXX
 PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN A. WU 01Jan2016	东莞市宇亮电子有限公司 DONG GUAN YU LIANG ELECTRONICS CO.,LTD	
DIMENSIONS: mm		CHEK S. CHIEN 01Jan2016		
TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ± 0.50 1 PLC ± 0.30 2 PLC ± 0.20 3 PLC ± 0.15 4 PLC ± - ANGLES ± 3°		APVD Abel 01Jan2016	NAME 0.80 PITCH 侧插母座 BOARD TO BOARD	
THIRD ANGLE PROJECTION		PRODUCT SPEC — WEIGHT —	SIZE A4	DRAWING No. YL007-011
CUSTOMER DRAWING			SCALE 1 : 1	SHEET 1 of 1